



Auxiliary contact, 1W, 2A, 250V AC

Part no. **ASAUXSC-SPM**
Article no. **131785**

Delivery program

| | | |
|-------------------|--|--|
| Product range | | Accessories |
| Products | | Auxiliary contact |
| Application field | | Residential buildings Utility buildings Open areas |
| For use with | | SPMT2PA |

Technical data ETIM 6.0

| | | |
|--|---|------------------|
| Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010]) | | |
| Device fitting | | - |
| Additional equipment | | Auxiliary switch |
| Attached at delivery | | No |
| Assembly width (TE) | | 0.5 |
| Number of normally open contacts | | 0 |
| Number of normally closed contacts | | 0 |
| Number of change-over contacts | | 1 |
| Number of fault-signal switches | | 0 |
| Rated switch current | A | 2 |
| Nominal rated voltage | V | 250 |
| Control voltage type | | AC |
| With autotest for earth leakage function | | No |
| Suitable for max. number of poles main contact unit (total) | | 1 |
| Suitable for max. current main contact unit | A | 0 |