
CoreLine Recessed Spot RS140


CE | indoor | 220V 240V | 50Hz 60Hz | LEDs | IK02 | Max. 35 °C Min. 0 °C | GLOW WIRE 650 °C


	P(W)	Ø mm	kg
RS140B LED6S fixed	11	78	0.54
RS141B LED6S adjustable	11	80	0.56
RS141B LED7S adjustable	16	80	0.56
RS141B LED12S adjustable	16	80	0.56


Fixed



Adjustable










4441 700 92851
© 2 / 2016, Philips Lighting Holding B.V. All rights reserved
Data subject to change without notice
Printed in The Netherlands
www.philips.com/lighting


PHILIPS








! The luminaire shall, under no circumstances, be covered with insulating matting or similar material.





Electrical Characteristics

Imax(A)	7
Tref(µs)	300
MCB	DownlightsMax.
B-10A	25
B-13A	32
B-16A	40
C-10A	40
C-13A	54
C-16A	68

- The luminaire shall be installed by a qualified electrician and wired in accordance with the latest IEE electrical regulations or the national requirements.
- Only to be installed outside arms reach as recessed ceiling luminair.
- For complete and updated list of advised dimmers, please check the CoreLine Recessed Spot RS140 page on the Philips Lighting eCatalog: http://www.ecat.lighting.philips.com